

## TRI PROOF SERIES

### IP66 LED LINEAR TRI PROOF LIGHTS

The Lightwell LED Vapour Proof Batten range is incredibly durable and has an Ingress Protection rating of IP66 which means it is completely dust tight and offers full protection against powerful water jets. The sturdy yet lightweight aluminium backing provides efficient heat dissipation but also generates a protective oxide coating which is highly corrosion resistant making this light perfect for use in any Commercial/Industrial setting.

#### PRODUCT FEATURES

- ✓ IP66 rated for indoor & outdoor applications
- ✓ Lightweight aluminium backing for effective heat dissipation
- ✓ Protective oxide coating
- ✓ Impact resistant polycarbonate housing
- ✓ Energy savings & reduced maintenance
- ✓ Environmentally friendly: no mercury or hazardous substances

20W

40W

60W

80W



#### Application

Factory lighting, Stockroom lighting, Retail lighting, Sports center lighting, Petrol station lighting, Supermarket lighting, Stadium lighting, School lighting, Car Parks, Outdoor areas.

Code	Power	Kelvin	Colour	Lumens	Lm/W	Dimensions	Beam	IP	Input	Emergency	Dimmable
TRI/IP66/600/NWND	20W	4000K	Natural White	1900	95	600*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/600/CWND	20W	6000K	Cool White	1900	95	600*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/1200/NWND	40W	4000K	Natural White	3800	95	1200*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/1200/CWND	40W	6000K	Cool White	3800	95	1200*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/1500/NWND	60W	4000K	Natural White	5700	95	1500*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/1500/EM/NWND	60W	4000K	Natural White	5700	95	1500*90*63mm	120°	IP66	AC240V	✓	X
TRI/IP66/1500/CWND	60W	6000K	Cool White	5700	95	1500*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/1500/EM/CWND	60W	6000K	Cool White	5700	95	1500*90*63mm	120°	IP66	AC240V	✓	X
TRI/IP66/1800/NWND	80W	4000K	Natural White	7600	95	1800*90*63mm	120°	IP66	AC240V	X	X
TRI/IP66/1800/CWND	80W	6000K	Cool White	7600	95	1800*90*63mm	120°	IP66	AC240V	X	X



#### ATTRIBUTES

Wattage:	20W, 40W, 60W, 80W
Power Factor:	>0.93
Input Voltage:	AC240V
Beam angle:	120°
Colour Temperature:	4000K / 6000K
IP Rating:	IP66
CRI:	>80 Ra
Dimmable:	No
LED Type:	Linear LED
Operating Temperature:	-30° ~ 50°
Frequency:	50/60Hz